The new FLEX Giraffe®. Light as air and best by far.





Lighter than any other.

Intelligent use of materials and weight-optimised design: at 3.9kg, the FLEX Giraffe® is almost a whole kilo lighter than its predecessors. This enables better handling and effortless working on high ceilings as well as on walls.



As versatile as your tasks.

Incredibly variable: the new FLEX Giraffe® is exceptionally flexible for various uses. This saves time and often makes special machinery redundant.

Convenient: extendible for ceilings up to 3.20 metres.



Time-saving: sand right to the edge – thanks to the close-edge segment.



The new FLEX Giraffe®. The handiest ever.

Lighter, handier and more robust than ever: the fully redesigned FLEX Giraffe® impresses painters, plasterers, drywall builders and renovators with its high user comfort, versatility and reliable quality – made in Germany.



The spring-mounted brush rim prevents sanding marks during application and ensures optimum dust extraction.



Cardanic suspension

The gimbal-mounted sanding head with optimised joint guarantees excellent flexibility and optimal adjustment to walls and ceilings.



Rotating close-edge sanding head*

Whether sanding edges or wall-ceiling transitions: you can now also sand in places that previously required subsequent sanding either by hand or with special machinery. This makes the new FLEX Giraffe® so unique.

Flexible drive shaft

... from engine to sanding disc: for reliable transmission, excellent flexibility and minimal weight on the head of the Giraffe for easy handling.

This makes the new FLEX Giraffe® so unique.

- Extremely light only 3.9 kg
- Optimally balanced for comfortable handling
- Easily extendible for high flexibility
- Close-edge sanding head* for universal application
- Innovative bag for easy transportation

* with model GE 5



Full wave electronics

The speed control allows you to adjust the speed during sanding, while the full wave electronics maintain a constant speed under pressure. Furthermore: overload protection thanks to power regulation.



The new FLEX Giraffe®: Pleasingly efficient

- Wide range of uses can eliminate the need for special machinery
- Adapted accessories increases efficiency
- Top efficiency for a long service life
- Extremely light machine tool ensures longer operating times

Ergonomic guide tube

VERE.

Comfortable handling thanks to the slim, oval-shaped guide tube with recessed grip – also available with a simple extension for maximum working heights of up to 3.20 metres.



GIRAFFE®

Innovative suction connection

Direct connection of the vacuum hose with the FLEX clip system.

On/Off switch

Acceleration switch for a slow and sensitive start – with locking device for continuous use.

D-shaped handle

... for flexible and comfortable work.

Protects the hose against kinks when stopped.

Extension

Thanks to the tool-free, click-in extension, the new FLEX Giraffe® can also sand at room heights of up to 3.2 metres comfortably and safely.

The new FLEX Giraffe® GE 5/GE 5 R:

TECHNICAL DATA	
Sanding head diameter max.	225 mm
Idle speed	1,100 - 1,650 min ⁻¹
Power consumption	500 watt
Tool holder	Velcro-backed sanding disc
Insertable	extension, 500 mm
Angle of inclination on head	100°
Adjustable	speed regulation, 6 settings
Length (90° disc)	1,520 mm
Weight	3.9 kg
Connecting cable	H07 RN-F, 5 m