

Specifications Sheet – Husqvarna 445E

Engine

Power output

2.1 kW

Cylinder displacement

45.7 cm³

Maximum power speed

9000 rpm

Idling speed

2700 rpm

Torque, max.

2.4 Nm

Torque, max. at rpm

6300 rpm

Clutch engagement speed (± 120)

4300 rpm

Fuel consumption

481 g/kWh

Fuel consumption

0.98 kg/h

Spark plug

Champion RCJ7Y, NGK BPMR7A

Electrode gap

0.5 mm

Ignition module air gap

0.3 mm

Oil pump type

Fixed flow

Equipment

Bar length (inch)

18"

Chain speed at 133% of maximum engine power speed

23 m/s

Sprocket type

Spur 7

Bar mount

Small

Recommended bar length, min-max

13-20 in

Dimensions

Weight (excl. cutting equipment)

5.1 kg

Lubricant

Oil tank volume
0.26 l

Sound and Noise

Sound power level, guaranteed (LWA)

114 dB(A)

Sound power level, measured

112 dB(A)

Sound pressure level at operators ear

103 dB(A)

Vibration

Equivalent vibration level (ahv, eq) front handle

3.1 m/s²

Equivalent vibration level (ahv, eq) rear handle

4.9 m/s²