

President® 5000 AL S19 Combo IC

Code #564740

Overview

Specifications



Masport's Industry best warranty on this lawnmower



[Click here for full warranty terms](#)

If you want the finest mower around then this model is very difficult to go past. It's strong, reliable and built to last with a commercial grade 190cc Briggs & Stratton engine with a 4 year warranty.

- Cut, Catch & Mulch
- Powered by Briggs & Stratton 190cc OHV Series 850 Professional IC ReadyStart™ 4 Stroke engine
- ReadyStart™ - no priming required and easy starting
- Cast iron sleeve in cylinder
- 485mm (19") heavy duty aluminium non rust chassis
- Masport Quadcut® 4 Blade Disc System for superior catching due to increased airflow
- Front 200mm (8") and Rear 200mm (8") adjustable dual bearing wheels
- Comfortable upturned upper handle with soft grip
- Reinforced lower handle for added strength
- Camlocks for quick release handle fold down
- Handle Lift System for easy catcher removal and storage
- HDPE Plastic Catcher with 'full' indicator
- Steel rear flap
- Zone start for comfortable starting position
- Masport Dual Mowzone® for edge to edge cutting for edge to edge cutting
- Washport to facilitate cleaning

- Mulching Capable ✓
- Handle Lift System ✓
- Adjustable Wheel Bearings ✓
- Catcher 'Full' Indicator ✓
- HDPE Plastic Catcher ✓
- Masport Dual Mowzone® ✓
- Zone Start ✓
- Deck Washport ✓

Specifications

Chassis Material	Aluminium
Cutting Methods	Cut, Catch, Mulch
Cutting Width	485mm (19")
Cutting System	Masport Quadcut® Blade Disc System
Number of Blades	4
Engine Make	Briggs & Stratton
Engine Model	OHV Series 850 Professional IC
Engine Capacity	190cc
Power Rating (Torque)	8.5ft/lb or 11.5Nm
Starting System	ReadyStart™
Engine Type	4 Stroke
Drive System	Push
Catcher Type	HDPE Plastic
Catcher Volume	42L
Wheel Type & Size	MSV® Mag Front 200mm (8") and Rear 200mm (8")
Wheel Bearing Type	Adjustable Dual Ball

Upper Handlebar Type	Upturned with soft grip and Handle Lift System
Lower Handlebar Type	Reinforced
Handlebar Retainer	Camlocks
Cutting Height Range	8mm - 73mm
Cutting Height Steps	11
Cutting Height Adjustment	Single Point
Weight	33.6kg
