

## REQUIRED SAFETY EQUIPMENT



Foot Protection



Hearing Protection



Hand Protection



Protective Clothing



Eye Protection



Shock Protection

## SAFETY FIRST

If you are collecting the equipment for someone else please make sure this sheet is given to the equipment user to read. This sheet should be given to the site supervisor if the equipment is being hired for commercial use so that the information is available to all users.

**Before starting any job, be sure to spend a few minutes planning and understanding the hazards and risks of the job. Do this by:**

- Thinking about and observing your surroundings
- Running through the steps of the job in your mind
- Identifying the hazards, how you can get hurt and how you'll prevent it
- Knowing what plant and equipment you need
- Only starting when you can do the job safely
- Ensuring you are trained or experienced for the task
- Communicating with everyone involved

**Points to consider when planning a task. Can you:**

- Come into contact with an energy source (e.g. heat, electricity, substance under pressure) or hazardous materials
- Be struck-by or against anything?
- Be caught-in, on or between anything?
- Slip, trip or fall on the same or too a lower level
- Strain or sprain a muscle?
- Cause damage to plant equipment or property?
- Spill or pollute something?

# Pump 50mm-75mm Flexi Drive & Motor Unit (Petrol)

## Instructions for Use



### Pre-Start Checks and Safety

- Check fuel tank is full of appropriate fuel and cap secures correctly
- Check for loose nuts, bolts and screws
- Check the connector locking pin is working correctly
- Make sure the flexi shaft pump head, motor and discharge hose are connected securely
- Make sure the job site is safe to operate

### When Operating

- Use appropriate PPE
- Ensure all by standers and assistance are aware of work proceedings
- Ensure the discharge hose is confined to the workspace
- Minimise sharp bends or curves in driveshaft

### Starting Procedure

- Connect the Flexible Pump
- Make sure the connector is located and locked correctly
- Turn the engine switch to ON
- Turn the fuel tap to ON
- Open the choke lever (cold start)
- Open the throttle lever to 1/2
- Pull the start rope cord
- Return the choke lever to OFF
- Open the throttle lever to FULL

### Stopping and After Use

- Return the throttle lever to OFF
- Turn the engine switch to OFF
- Turn the fuel tap to OFF
- Disconnect the Flexi Pump
- Let the unit cool down
- Make sure the unit is clean