

# KX

# KX41-3V

# SPECIFICATIONS

## Specifications

Model		KX41-3V		
Type of ROPS / FOPS		Canopy		
Type of tracks		Rubber		
Engine	Model	Kubota D902-E3		
	Output (SAEJ 1995 gross)	HP (kW)/rpm	17.0 (12.7) / 2300	
	Output (SAEJ 1349 net)	HP (kW)/rpm	15.2 (11.3) / 2300	
	Displacement	cu.in. (cc)	54.80 (898)	
Dimensions	Overall length	ft.in. (mm)	12'0" (3660)	
	Overall height	ft.in. (mm)	7'5.6" (2280)	
	Overall width	ft.in. (mm)	4'3.2" (1300) / 3'3.0" (990)	
	Min. ground clearance	in. (mm)	6.3" (160)	
Hydraulic system	Pump capacity	gpm. (ℓ /min)	4.6 (17.3) × 2 / 2.8 (10.4) × 1 / 1.7 (6.2) × 1	
	Auxiliary hydraulic flow	gpm. (ℓ /min)	7.4 (27.7)	
	Max. breakout force	Bucket / Arm	lbs. (kgf)	3505 (1590) / 1748 (793)
Drive system	Travel speed	Low / High	mph (km/h)	1.5 (2.3) / 2.6 (4.1)
	Max. traction force		lbs. (kgf)	4310 (1961)
	Tumbler distance		ft.in. (mm)	4'1" (1230)
	Crawler length		ft.in. (mm)	5'3" (1590)
	Shoe width		in. (mm)	9.1" (230)
	Ground contact pressure		psi (kgf/cm <sup>2</sup> )	3.8 (0.27)
Swing system	Unit swing speed		rpm	9.1
	Boom swing angle	Left / Right	degree	73 / 50
Blade	Dimensions	Width	in. (mm)	4'3.2" (1300) / 3'3.0" (990)
		Height	in. (mm)	9.1" (230)
	Max. lift above ground		in. (mm)	7.5" (190)
	Max. drop below ground		in. (mm)	8.3" (210)
Hydraulic oil (reservoir/system)		gpm. (ℓ)	3.7 (14) / 7.1 (27)	
Fuel reservoir		gpm. (ℓ)	5.6 (21)	
Operating weight (Including operator's weight 175 lbs.)		lbs.(kgf)	3693 (1675)	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty information. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt for almost all applications.

## DIMENSIONS

