## Specifications Sheet – Husqvarna 576XP

## **Engine**

Power output

4.2 kW

Cylinder displacement

73.5 cm<sup>3</sup>

Maximum power speed

9600 rpm

Idling speed

2700 rpm

Torque, max.

4.5 Nm

Fuel consumption

417 g/kWh

Fuel consumption

1.77 kg/h

Spark plug

**NGK BPMR7A, Champion RCJ7Y** 

Electrode gap

0.5 mm

Oil pump type

**Automatic** 

# **Equipment**

Bar length (inch)

28"

Recommended bar length, min

38 cm

Recommended bar length, max

70 cm

Chain speed at max power

21 4 m/s

Chain speed at 133% of maximum engine power speed

28.5 m/s

Sprocket type

Rim 7

### **Dimensions**

Weight (excl. cutting equipment)

6.9 kg

#### Lubricant

Oil tank volume

0.4 I
Oil pump type

Automatic
Oil pump capacity Max

22 ml/min
Oil pump capacity Min

5 ml/min

### **Sound and Noise**

Sound power level, guaranteed (LWA)
116 dB(A)
Sound power level, measured
114 dB(A)
Sound pressure level at operators ear
105 dB(A)

#### **Vibration**

Equivalent vibration level (ahv, eq) front handle **5.1 m/s²**Equivalent vibration level (ahv, eq) rear handle **4.8 m/s²**