

TECHNICAL DATA

Technical data

	536LiL	536LiR
Motor		
Motor type	BLDC (brushless) 36V BLDC (brushless) 36V	
Speed of output shaft, rpm	5500	5500
Cutting width, mm	400	400
Weight		
Weight without battery, kg	3	3,8
Weight with battery, kg	4,2	5
Battery runtime		
Battery runtime, min, (free run) with SavE activated	60	60
Noise emissions		
(see note 1)		
Sound power level, measured dB (A)	92	92
Sound power level, guaranteed L _{WA} dB (A)	96	96
Noise levels		
(see note 2)		
Equivalent sound pressure level at the operator's ear, measured according to EN ISO 60335-91-2 and ISO 22868, dB(A):	81	76
Vibration levels		
(see note 3)		
Vibration levels at handles, measured according to ISO 22867, m/s ²		
Equipped with trimmer head (original), left/right	1.7/0.5	2.6/2.1

Use only a Husqvarna original BLi battery in your machine.

Approved chargers for the specified batteries, BLi.		
Battery charger	QC120	QC330
Mains Voltage, V	220-240	100-240
Frequency, Hz	50-60	50-60
Power, W	125	330

Note 1: Noise emissions in the environment measured as sound power (L_{WA}) in conformity with EC directive 2000/14/EC. The difference between guaranteed and measured sound power is that the guaranteed sound power also includes dispersion in the measurement result and the variations between different machines of the same model according to Directive 2000/14/EC.

Note 2: Reported data for equivalent sound pressure level for the machine has a typical statistical dispersion (standard deviation) of 3 dB (A).

Note 3: Reported data for equivalent vibration level has a typical statistical dispersion (standard deviation) of 2 m/s².

Approved accessories	Type	Cutting attachment guard, Art. no.
Trimmer head	T25B (Ø 2.0 mm line)	577 01 83-01