






SPECIFICATION DATA SHEET | MODEL : 30TCG



Extend the run times of your diesel powered equipment with the **TRANSCUBE™ 30TCG**. *Increased Efficiency + Decreased Expenses = Maximized Revenue.*

-  **Transportable.** Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the tank full of fuel.
-  **Stackable.** Easily stackable (2)-high full of fuel and (3)-high empty to reduce storage space requirements.
-  **Accessible.** Access manway for maintenance and inspection of inner tank. Removable inner tank for servicing and cleaning.
-  **Efficient.** Lockable equipment cabinet locks and secures equipment and fuel ports to run up to 3 pieces of diesel-powered equipment.
-  **Environmentally Safe.** Double-walled, 110% containment eliminates the need for spill pans, UL 142 approved.

SPECIFICATIONS*	
STANDARD FITTINGS: High accuracy contents gauge; 3" Fill Point; 2" fusible link fill port; 1" pump feed with flexible dip pipe, strainer & non-return valve; (1) engine feed and return port set; pressure/vacuum vent; breather vent. OPTIONAL FITTINGS: Complete transfer pump kits; water & particulate filter kits; fuel up to (2) feed & return blocks; fuel hose & quick couplers.	
Capacity (Brim-Fill) Litres: 3000	Dimension Height (mm/in): 1315 mm/51.77"
Capacity (Brim-Fill) Imperial Gallons: 660	Weight Empty (lbs/kg): 2234 lbs (1013kg)
Capacity (Brim-Fill) US Gallons: 793	Weight Full (lbs/kg): 8855 lbs (4016kg)
Dimension Length (mm/in): 2298 mm/90.45"	Approvals: UL142, ULC S-601-07, SUN IBC Type 31A,
Dimension Width (mm/in): 1548 mm/60.94"	UN DOT, NFPA, Transport Canada, Vlare, Kiwa

*Model specifications may slightly differ based on stock availability in your area. Please contact your local representative to confirm tank specifications.

