Assessment No: G001



Company Name: **GreenMech Ltd** Activity: Arborist 150

Hazard	At Risk	Consequence (C)	Likelihood (L)		Risk	Controls	Rev	ised	Final
	Those likely	Likely injury	Rating	Of incident	Rating	Score		С	L	Risk
	to be affected	from hazard						Rating	Rating	Score
ENTANGLEMENT With cutter in base of CHIPPER infeed chute	OPERATOR	FATALITY – LOSS OF LIMB	5	VERY LIKELY	5	25	Reach area safety distance to cutter complies to latest HSE guidelines. Fix safety stop rail to upper and side perimeter on infeed chute. Operation of this emergency stop system should operate as recommended by HSE. Only appointed operators to use machine (competent)	5	2	10
STABBING AND PUNCTURE by projectiles from cutter. Wood, stones, nails rebound back out of infeed chute	OPERATOR	Injuries to face, eyes, head and hands	3	PROBABLE	4	12	Trained Operator. Check only green waste is fed into machine. Safety helmet to BSEN 397 Forestry visor Hard wearing gloves	3	2	6

Consequence	Score	Likelihood	Score	To find risk Score multiply consequence rating by the likelihood rating
Fatality	5	Very likely	5	Final revised risk score acceptable to the
Disability	4	Probable	4	company is 10 or less. If higher, further
Very serious (broken limbs)	3	Possible	3	controls are required.
Important (3 day accident)	2	Remotely possible	2	Final revised likelihood score must be 2 or less
Noticeable (first aid)	1	Improbable	1	

Signed:	
Date:	
Review Date:	

Assessment No: G001-2



Company Name: **GreenMech Ltd** Activity: Arborist 150

Hazard	At Risk	Consequence (C	C)	Likelihood (L)		Risk	Controls	Rev	ised	Final
	Those likely	Likely injury	Rating	Of incident	Rating	Score		С	L	Risk
	to be affected	from hazard						Rating	Rating	Score
NOISE Guaranteed sound pressure level of Lwa 100dB	OPERATOR THIRD PARTY	NOISE INDUCED HEARING LOSS	4	PROBABLE	4	16	Wear hearing protection to BE EN 352-3. Display mandatory 'wear hearing protection' sign	4	2	8
VIBRATION – movement of machine	OPERATOR	BROKEN OR BRUISED LIMB	3	POSSIBLE	3	9	Trained Operator. Lock off handbrake Chock wheels and secure stabiliser in place Stand machine on sound level ground	3	2	6
STABBING – PUNCTURE When operating handle to raise engine – residue from exhaust chutte	OPERATOR THIRD PARTY	EYE INJURIES CUTS TO FACE	2	POSSIBLE	3	6	Cordon off collection point. Operator to wear head and face protection	2	1	2

Consequence	Score	Likelihood	Score	To find risk Score multiply consequence rating by the likelihood rating
Fatality	5	Very likely	5	Final revised risk score acceptable to the
Disability	4	Probable	4	company is 10 or less. If higher, further
Very serious (broken limbs)	3	Possible	3	controls are required.
Important (3 day accident)	2	Remotely possible	2	Final revised likelihood score must be 2 or less
Noticeable (first aid)	1	Improbable	1	

Assessment No: G001-3



Company Name: **GreenMech Ltd** Activity: Arborist 150

Hazard	At Risk	Consequence (C	<u>;)</u>	Likelihood (L)		Risk	Controls	Rev	ised	Final
	Those likely	Likely injury	Rating	Of incident	Rating	Score		С	L	Risk
	to be affected	from hazard						Rating	Rating	Score
ENTANGLEMENT Branches with clothing	OPERATOR	Drawn into cutters – FATALITY – LOSS OF LIMBS	5	POSSIBLE	3	15	Wear snug fitting clothes. No ties, scarves etc. Same controls as for previous hazard of entanglement with cutters. Wear gloves with long cuffs which can be tucked into sleeves	5	2	10
STABBING AND PUNCTURE – Processed green waste	OPERATOR THIRD PARTY	EYE INJURIES, CUTS TO FACE	1	POSSIBLE	3	3	Trained operator Lock off exhaust chute Cordon off collection point	1	1	2
STABBING AND PUNCTURE – Handling branches	OPERATOR	CUTS TO HANDS	2	QUITE POSSIBLE	4	8	Wear hard wearing gloves with long cuffs that can be tucked into sleeves.	2	2	4

Consequence	Score	Likelihood	Score	To find risk Score multiply consequence rating by the likelihood rating
Fatality	5	Very likely	5	Final revised risk score acceptable to the
Disability	4	Probable	4	company is 10 or less. If higher, further
Very serious (broken limbs)	3	Possible	3	controls are required.
Important (3 day accident)	2	Remotely possible	2	Final revised likelihood score must be 2 or less
Noticeable (first aid)	1	Improbable	1	

Signed:	
Date:	
Review Date:	

Assessment No: G001-4



Company Name: **GreenMech Ltd** Activity: Arborist 150

Hazard	At Risk	Consequence (C	C)	Likelihood (L)		Risk	Controls	Rev	ised	Final
	Those likely	Likely injury	Rating	Of incident	Rating	Score		С	L	Risk
	to be affected	from hazard						Rating	Rating	Score
IMPACT	OPERATOR	BROKEN LIMB	3	POSSIBLE	3	9	Stand at side of machine.	3	2	6
Being struck by		BRUISES					Trained operator			
branch when										
feeding green										
waste into cutters			_		_			_		
CRUSH Adjusting height of A-frame	OPERATOR	BROKEN LIMB, BRUISES	3	POSSIBLE	3	9	Ensure hand brake is applied and wheels are chocked. Use winding handle to lower jockey	3	1	3
							wheel. Lower stabiliser and lock off			
CRUSH, IMPACT	OPERATOR	BROKEN LIMB,	3	Chute handled at	3	9	Trained operator, check	3	2	6
Dropping infeed		BRUISES		start and finish of			hinge points before use.			
chute when fixing				work			Use fasteners to secure			
in working position/							chute.			
transport position										

Consequence	Score	Likelihood	Score	To find risk Score multiply consequence rating by the likelihood rating
Fatality	5	Very likely	5	Final revised risk score acceptable to the
Disability	4	Probable	4	company is 10 or less. If higher, further
Very serious (broken limbs)	3	Possible	3	controls are required.
Important (3 day accident)	2	Remotely possible	2	Final revised likelihood score must be 2 or less
Noticeable (first aid)	1	Improbable	1	

Signed:	
Date:	
Review Date:	