

PowerSource Generators

Product Range




Doosan PowerSource

Performance you can trust

Doosan Infracore Portable Power is proud to present its complete new line of generators ranging from 20 to 500 kVA.

PowerSource delivers performance you can trust to power critical applications and offers innovative features that simplify operation, enhance serviceability, reduce downtime and promote environmental friendliness. The reliability of these generators combined with the dedicated Doosan Infracore Portable Power service support make PowerSource the best choice for tough applications.











Controls & Connections easy to use

All controls and power connections are consolidated at the rear of the unit for enhanced safety and convenience. The PowerSource control panel is easy to use, allows high degree of customisation and lets users manage generator output and many other functions for optimal performance.

Extended Runtime

The combination of high-capacity fuel tank and low fuel consumption allows PowerSource generators to run at least 24 hours without refueling, ensuring uninterrupted power to your critical applications and thereby reducing operating costs.



Compact/Accessibility

PowerSource generators are designed to be compact and quiet, and maximised performance while powering a full load in high temperature conditions. They are among the lightest and smallest of the industry thus reducing logistic and transport costs. Furthermore their large doors provide perfect accessibility and facilitate serviceability without compromising the compactness.

Easy to handle

All PowerSource models feature forklift pockets and lifting hooks that allow you to move and install your generator easily, quickly, safely and without damaging your investment.

Environmental friendliness

Each model features 110% environmental containment to prevent any spillage of fuel, oil, or coolant. In addition, PowerSource is equipped with Stage 2 engines. PowerSource achieves powerful high-output performance with low sound output, thanks to its innovative enclosure with sound-reducing insulation, optimized fan speeds and critical grade exhaust components.

Reliable

All PowerSource units feature powerful alternators with AREP excitation which gives best in class motor-starting capability. PowerSource features a heavy-gauge enclosure finished with a superior zinc rich primer and a durable powder final paint to provide the ultimate in corrosion resistance for long life and exceptional resale values. Finally, Doosan Infracore Portable Power intensive endurance testing procedures make PowerSource the most durable and reliable generators.



Contr	ol Panel Features G20 to G500	Analog	Digital
	AC voltage phase-phase	0	0
	AC voltage phase-phase and phase-neutral	Х	0
	AC amperes per phase	0	0
nts	Ammeter selector switch	0	0
Measurements	Frequency meter	0	0
	Running hours	0	0
ası	Fuel level	0	0
MA	Battery voltage	0	0
	Oil pressure	•	0
	Coolant temperature		0
	RPM (rotation per minute)	Х	0
IA.	Engine running	0	0
Indicators	Preglow	0	0
<u>ica</u>	ECU status (from G60 to G500)	0	0
lnd	In-auto light	0	Х
	Not-in-auto light	Х	0
	Low oil pressure shutdown	0	0
Shutdown & warnings	High coolant temperature shutdown	0	0
Ē	Low coolant level shutdown (from G160 to G500)	0	0
wa	Engine general fault shutdown (from G60 to G500)	0	0
8 -	Engine overspeed shutdown	0	0
Mo	Engine overcrank	0	0
utd	Low fuel warning/shutdown	0	0
-S	Battery charge fail warning	0	0
	High containment level warning	0	0
Miscellaneous	Panel lamp	0	0
	Buttons for start/stop/mode/fault reset	0	0
	Emergency stop shutdown	0	0
	Remote start/stop	0	0
	Engines diagnostic codes on display	Х	0
	Language selection	Х	0
	History capability (events/warning/shutdown)	Х	0





 \circ = Standard \blacksquare = Optional x = Not Applicable

Socket configurations:

1) European sockets G20 & G30:	1 X CE 1Ø 16A 230V	1 X CE 3Ø 16A 400V	1 X CE 3Ø 32A 400V
2) European sockets G40 to G500:	1 X CE 1Ø 16A 230V	1 X CE 3Ø 32A 400V	1 X CE 3Ø 63A 400V
3) UK sockets G20 to G30:	2 X CE 1Ø 16A 110V	1 X CE 3Ø 16A 400V	1 X CE 3Ø 32A 400V
4) UK sockets G40 to G500:	2 X CE 1Ø 16A 110V	1 X CE 3Ø 32A 400V	1 X CE 3Ø 63A 400V

1 X Schucco 1Ø 16A 230V 1 X Schucco 1Ø 16A 230V 1 X Room for additional socket 1 X Room for additional socket

1 X Room for additional socket



PowerSource Generators

Specifications





-							
Models		G20	G30	G40	G60	G80	
PERFORMANCE							
Prime power (kVA)		20	31	40	61	80	
Standby power (kVA)		22	31	42	65	88	
Frequency (Hz)		50	50	50	50	50	
Voltages, single phase / 3 phase (V)		230/400	230/400	230/400	230/400	230/400	
Maximum sound power level (LwA)		94	94	96	92	94	
Alternator		Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	
Alternator excitation type		AREP	AREP	AREP	AREP	AREP	
Insulation Class		Н	Н	Н	Н	Н	
Control Panel		Analog	Analog	Analog	Analog	Analog	
ENGINE							
Make		Mitsubishi	Mitsubishi	Mitsubishi	John Deere	John Deere	
Model		4IRQ2N	4IRS2N	4IRS2T	4IRD5T	4IRD5AE	
Prime power engine (kW)		21	29	38	55	75	
Number of cylinders		4	4	4	4	4	
Electrical system (V)		12	12	12	12	12	
Speed regulation accuracy (Steady State)		+ / - 2.5%	+/-2.5%	+/-2.5%	+ / - 2.5%	+ / - 0.25%	
Fuel tank usable capacity (L)		150	199	413	413	716	
Fuel consumption @ 75% Load (L/hr)		4.7	6.5	8.5	11.7	14.9	
Runtime @ 75% load (hr)		32	30.4	48.4	35.2	48.0	
WEIGHTS & DIMENSIONS							
Length (mm)		1862	2165	2471	2471	2720	
Width (mm)		889	1003	1003	1003	1214	
Height (mm)		1382	1448	1750	1750	1763	
Dry weight (kg)		846	1134	1260	1560	1714	
Wet weight (kg)		999	1329	1649	1949	2377	
STANDARD FEATURES							
Double-wall fuel tank		0	0	0	0	0	
Bunding capacity min.110% fluid		0	0	0	0	0	
Forklift pockets	1	0	0	0	0	0	
Two stage heavy duty air filter		0	0	0	0	0	
Earth rod & cable		0	0	0	0	0	
Central lifting point		0	0	0	0	0	
External emergency stop button		0	0	0	0	0	
Battery isolator switch	2	0	0	0	0	0	
Protective guard against hot spots		0	0	0	0	0	
Single 80% step load capability		0	0	0	0	0	
Oil sump pump		0	0	0	0	0	
4-pole circuit breaker		0	0	0	0	0	
Remote start		0	0	0	0	0	
Fuel water separator		0	0	0	0	0	
Rigid bus bar terminal (5 poles)		0	0	0	0	0	
Voltage adjusting potentiometer		0	0	0	0	0	
Low level coolant shutdown		×	×	×	×	×	
Earth leakage protection		Fixed 300 mA	Fixed 300 mA	Fixed 300 mA	Adjustable	Adjustable	
OPTIONS		1 included in it	· ixed 500 · iii ·	· incusoriii ·	ragastasie	, tajastas.e	
Digital control panel	3						
Synchronization panel	4	×	×	×	×	×	
Adjustable earth leakage protection		^			0	0	
Sockets	6	Δ	Δ	Δ	Δ	Δ	
3 way fuel valve		Δ	Δ	Δ	Δ	Δ	
Super Start Package (Block/jacket heater and Battery charger)		Δ	Δ	Δ	Δ	Δ	
Refinery Kit (Spark arrestor option and Air Shut off valve)		×				Δ.	
		×	X	X	X	0	
Electronic governor		×	×	×	×	0	
		×	× •	× •	× •		



G100	G160	G200	G250	G400	G500
105	150	200	250	410	500
105	158	200	259	410	500
111	174	220	294	437	550
50	50	50	50	50	50
230/400	230/400	230/400	230/400	230/400	230/400
96	95	97	97	98	99
Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer	Leroy Somer
AREP	AREP	AREP	AREP	AREP	AREP
Н	Н	Н	Н	Н	Н
Analog	Analog	Analog	Analog	Analog	Analog
John Deere	John Deere	John Deere	Cummins	Cummins	Cummins
4IRD5AE	6IRF8AE	6IRF8AE4	QSL9-G3	QSX15-G8	QSX15-G8
94			-	-	444
	139	188	227	358	
4	6	6	6	6	6
12	12	12	24	24	24
+/-0.25%	+/-0.25%	+/-0.25%	+/-0.25%	+/-0.25%	+/-0.25%
716	961	961	1461	2173	2173
17.6	25.1	30.4	49.4	65.2	78.7
40.7	38.3	31.6	29.6	33.3	27.6
2720	3566	3566	4049	5037	5037
1214	1265	1265	1425	1623	1623
1763	2017	2017	2385	2548	2548
1951	2678	2785	3441	5622	5749
2614	3567	3674	4783	7619	7746
2014	3307	3074	4/03	7019	7740
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
0	0	0	0	0	0
		0			
0	0	0	0	0	0
X Adianatalala					
Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
	•	•		•	•
×	×	×		•	
0	0	0	0	0	0
Δ	Δ	Δ	Δ	Δ	Δ
Δ	Δ	Δ	Δ	Δ	Δ
Δ	Δ	Δ	Δ	Δ	Δ
0	0	0	0	0	0
	×	×	×	×	×
-			•		
_	_	_	_	_	_









Product improvement is a continuous goal at Doosan Infracore Portable Power. Specifications and design are subject to change without notice or obligation. All dimensions in mm.



The PowerSource journey at Doosan starts here







Warranty

Doosan Infracore Portable Power protects your purchase or lease with a 1 year or 2,000 hours warranty (whichever first occurs) on the entire package, 2 years or 4,000 hours on the alternator as well as 2 years or 4,000 hours on Mitsubishi and John Deere engines (G20 to G200) and 2 years or 2,000 hours on Cummins engines (G250 to G500).

Aftermarket solution

- Dealer stocking program for frequently-used parts
- Express availability for other parts
- Factory technical support (available at our manufacturing plant for all product lines)
- Supporting you and your dealer with troubleshooting expertise on difficult service problems

Financial solutions

Financing and leasing options tailored to meet your individual business needs. Our streamlined loan application and credit approval process can quickly make your business plans a reality.

Re-marketing services

Doosan Infracore Portable Power offers services to all its clients to help them to sales any of their used equipment by giving them a direct online connection to a vast inventory of pre-owned equipment, anywhere in the world.

At Doosan Infracore Portable Power, you are not just buying a powerful piece of equipment. You are investing in the strength of Doosan Infracore Portable Power and its people. From engineers and factory technicians, to field representatives and your dealer, we support your purchase. We are committed to helping you realize maximum value job after job, day after day. Wherever you see a piece of Doosan Infracore Portable Power equipment, you'll know that all of Doosan Infracore Portable Power team is behind it.

Our industry-leading support system will keep you up and running for as long as you own your Doosan Infracore Portable Power equipment.

Doosan Infracore Portable Power is committed to supporting the product throughout its life. We are dedicated to providing you and your business an invaluable source for product information, financial service, training, technical service bulletins, service, parts and more...

More than generators



www. doos an portable power. com

