## **Plate Compactor**

- \*Environmentally friendly product design.
- \*From the MVC-F60 to the MVC-98D, the series comprises a wide range of products to meet customers needs in a variety of sites.
- \*The Mikasa VAS plate compactor range features handles with Mikasa's original vibration absorbing system.




LINE UP


MVC-F70R/H MVC-40G MVC-50GB MVC-F80R/H MVC-88GE/GH MVC-98D

Plate Compactor

**SPECIFICATIONS** 

OPTION







	Capacity for		
	50GB	8.5 ℓ	
4	F60·F70	11 &	
	F80	13ℓ	
" / *	F82	11 &	
C miles	88-98D	13 l	

model	dimensions	plate size	vibrating frequency	centrifugal force(max.)	max. traveling speed	limited gradeability (max)	power source
MVC-40G (Folding Handle)	H : 920mm H1 : 590mm L : 855mm <b>WT : 46kg(47kg)</b>	W : 290mm L1 : 420mm	103Hz (6,200V.P.M)	7.2kN (730kgf)	25m/min	35%	Robin EH09-2F max.output 2.1kw(2.8PS)
MVC-50GB (Folding Handle) <folding <br="" handle="">water tank&gt;</folding>	H : 920mm H1 : 545mm L : 865mm <l: 925mm=""> WT : 59kg(60kg)&lt;67kg&gt;</l:>	W : 345mm L1 : 460mm	97Hz (5,800V.P.M)	9.8kN (1,000kgf)	25m/min	35%	Robin EX13D max.output 3.2kw(4.3PS)
MVC-F60 R/H	H : 860mm H1 : 590mm L : 905mm WT : 74/73kg	W : 350mm L <sub>1</sub> : 510mm	93Hz (5,600V.P.M)	10.1kN (1,030kgf)	25m/min	35%	Robin EX13D max.output 3.2kW(4.3PS) Honda GX120 max.output 2.6kW(3.5PS)
MVC-F70 R/H	H : 860mm H1 : 590mm L : 905mm <b>WT : 81kg</b>	W : 420mm L <sub>1</sub> : 510mm	93Hz (5,600V.P.M)	12.0kN (1,220kgf)	25m/min	35%	Robin EX17D max.output 4.2kW(5.7PS) Honda GX160 max.output 3.6kW(4.9PS)
MVC-F80 R/H	H : 860mm H1 : 570mm L : 915mm <b>WT : 87kg</b>	W : 450mm L <sub>1</sub> : 570mm	93Hz (5,600V.P.M)	13.7kN (1,400kgf)	25m/min	35%	Robin EX17D max.output 4.2kw(5.7PS) Honda GX160 max.output 3.6kW(4.9PS)
MVC-88 GE/GH	H : 825mm H1 : 560mm L : 1,100mm <b>WT : 96kg</b>	W : 500mm L <sub>1</sub> : 525mm	100Hz (6,000V.P.M)	15.0kN (1,530kgf)	25m/min	35%	Robin EX17D max.output 4.2kW(5.7PS) Honda GX160 max.output 3.6kW(4.9PS)
MVC-98D	H : 825mm H <sub>1</sub> : 650mm L : 1,100mm <b>WT : 108kg</b>	W : 500mm L <sub>1</sub> : 525mm	100Hz (6,000V.P.M)	15.0kN (1,530kgf)	25m/min	35%	Yanmar L48N max.output 3.5kW(4.7PS)

Weight includes weigh of machine, lubricants, 50% of fuel and 50% of water in case with water tank option. Features and specifications are subject to change without notification.

MVC-40G: Water tank is not available.