11. Service data

11-1 Specifications

MODEL DCA SEEST DCA SEEST DCA 100 DO 1					
MODEL			DCA-25ESI	DCA-45ESI	DCA-100ESI
A C G E N E R A T O R	MODEL		DF-0270I DH-0480I DB-1101I		
	FREQUENCY		50 / 60 Hz		
	RATED OUTPUT		20 / 25 kVA	37 / 45 kVA	80 / 100 kVA
	RATED VOLTAGE		200/220 / 400/440 V		
	RATED CURRENT		57.7/65.6/28.9/32.8 A	107/118/53.4/59.0 A	231/262/115/131 A
	POWER FACTOR		0.8 (lagging)		
	NO.OF PHASES		Three-phase (four wire)		
	EXCITATION		Brushless type (with automatic voltage regulator)		
	NO.OF POLES		4		
	SPEED		1500 / 1800 min ⁻¹ {rpm}		
	INSULATION		class F	class H	class F
ENGINE	MANUFACTURE		ISUZU	ISUZU	ISUZU
	MODEL		AA-4LE2	BB-4JG1T	DD-6BG1T
	ТҮРЕ		4-cycle water cooled diesel engine ,direct injection	1 A CTICLO TRIPLOY COOLED decoral common descript	
	NO.OF CYLINDERS		4	4	6
	BORE×STROKE		85×96 mm	95.4×107 mm	105×125 mm
	TOTAL DISPLACEMENT		2.179 L	3.059 L	6.494 L
	RATED OUTPUT (1500/1800min ⁻¹)		19.1/23.5 kW	34.2/41.5 kW	73.6/91.3 kW
	BATTERY (DOMESTIC STANDARD)		80D26R	95D31R	95D31R×2
	FUEL		DIESEL FUEL ASTM No.2 or equivalent		
	FUEL TANK CAP.		70 L	100 L	225 L
	ENGINE OIL	OVERALL	8.5 L	10.0 L	22.4 L
	*1	FILTER	0.4 L	0.3 L	2.4L
	COOLANT	OVERALL	6.6 L	10.9 L	22.0 L
	QUANTITY *2	RESERVE TANK	0.9 L	0.9 L	1.0 L
S E T	LENGTH OVERALL		1540 mm	1900 mm	2750 mm
	WIDTH OVERALL		680 mm	880 mm	1050 mm
	HEIGHT		900 mm	1250 mm	1350 mm
	DRY WEIGHT		564 kg	960 kg	1730 kg
	TOTAL WEIGHT		642 kg	1070 kg	1970 kg

The above specifications and set dimensions are subject to change.

Dry weight: This weight does not contain the cooling water, engine oil and fuel.

Total weight: This weight contains the cooling water, engine oil and fuel.

^{*1} Overall of engine oil contains filter.

^{*2} Overall of coolant quantity contains reserve tank.