



**WACKER  
NEUSON**  
*all it takes!*



## 4-stroke rammer BS60-4As, 280 mm ramming shoe

5200018232

[Home](#) >> [Catalog](#) >> [Products](#) >> [Compaction](#) >> [Vibratory Rammers](#) >> [4 Stroke Rammer](#) >> [4-stroke rammer BS60-4As, 280 mm ramming shoe](#)

### 4-stroke rammer BS60-4As, 280 mm ramming shoe

Material number 5200018232

Four-stroke vibratory rammer with 280 mm ramming shoe for soil compaction, Honda GX engine



### Product details

- Long shoe stroke, high percussion rate and high impact energy with fast advance travel achieve high performance results
- Low oil protection: Unit will not start if sensor detects no oil or low oil, protecting the engine
- Simple operation with only one lever for acceleration and shutoff
- Powered by Honda GX 100 engine and designed for the compaction of cohesive, mixed and granular soils in confined areas
- Unique four-stage air filtration system provides longer life and improved durability

### Comes with

- Vibratory rammer
- Operator's Manual

## Technical specifications

### 4-stroke rammer BS60-4As, 280 mm ramming shoe

#### SHIPPING AND STORAGE

Shipping weight	80,00 kg
-----------------	----------

#### MECHANICAL - OUTPUT DETAILS

Number of blows	690 1/min
-----------------	-----------

#### MECHANICAL DETAILS

Length	673 mm
--------	--------

Length Ramming Shoe	336 mm
---------------------	--------

Width	343 mm
-------	--------

Width Ramming Shoe	280 mm
--------------------	--------

Height	965 mm
--------	--------

Weight	72,00 kg
--------	----------

stroke at tamper	78 mm
------------------	-------

#### ENVIRONMENT DATA

Sound level LpA	91,0 dB(A)
-----------------	------------

Sound power LWA, measured	104,0 dB(A)
---------------------------	-------------

Sound level LpA (Standard)	EN 500-4
----------------------------	----------

Sound power LWA, guaranteed	108,0 dB(A)
-----------------------------	-------------

Sound power LWA (Standard)	2000/14/EG
----------------------------	------------

HAV summation (Standard)	EN ISO 5349-1
--------------------------	---------------

HAV summation (average value)	6,5 m/s <sup>2</sup>
-------------------------------	----------------------

#### ENGINE

Cooling	air cooling
---------	-------------

Engine type	Gasoline engine
-------------	-----------------

Engine operating mode	four-stroke
-----------------------	-------------

Cylinder capacity	98 cm <sup>3</sup>
-------------------	--------------------

Fuel	Gasoline
------	----------

Fuel management	Carburettor
-----------------	-------------

Fuel consumption	0,90 L/hr
Cylinder	1
Tank capacity	3,0 l
Oil specification	SAE 10W-30
Oil filling max.	0,40 l
Operating power	2,4 KW
Effective power	2,4 KW
Oil filling min.	0,40 l
Operating Engine speed	4.200 1/min
Exhaust-gas limit	EPA Phase2 & EU2002/88/EC
Fuel injection pump type	0,6 - 0,7 mm
Oil volume incl. filter change	dry air filter
Starter Voltage	Recoil starter
Speed max.	Honda
Electrode distance	0,6 - 0,7 mm

#### Custom Attributes

Model serie	BS60-4
-------------	--------

#### Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE