



S130
SKID-STEER
LOADER



Bobcat® \$130 Skid-Steer Loader

PECIFICATIONS

Performance

Rated Operating Capacity ROC with optional counterweight Tipping Load Hydraulic Pump Capacity Operating Weight

Dimensions

Length (with bucket) Width (with bucket) Height Height to Bucket Pin

Engine

Make/Model Fuel/Cooling Cylinders SAE NET HP/Displacement **Fuel Tank Capacity**

Operation

Steering and Drive

Hydraulics

Transmission

Standard Features

Options/Accessories

S130

1300 lb. (590 kg) 1400 lb. (635 kg) 2600 lb. (1179 kg) 16.9 GPM (64.0 L/min) 7.3 MPH (11,7 km/hr.) 4740 lb. (2150 kg)

120.5 in. (3059 mm) 55.0 in. (1398 mm) 77.0 in. (1956 mm) 109.1in. (2771 mm)

Tier II Compliant

Kubota V2203-DI Diesel/Liquid 46/134 in.3 (2,2 L) 14 gal. (53 L)

Forward, reverse, travel speed and steering controlled by two hand levers

Raise/lower lift arms and dumn/rollback bucket controlled by two foot pedals or optional hand controls Hydrostatic four-wheel drive

Adjustable Cushion Seat Automatically Activated Glow Plugs Bobcat Interlock Control System (BICS™) Bob-Tach™ Deluxe Cab Dual Path Cooling System Engine/Hydraulic Shutdown Front Auxiliary Hydraulics

Advanced Control System (ACS) Attachment Control Kit Backup Alarm Bobcat Heavy-Duty Tires Bobcat Heavy-Duty

Offset Tires Offset Tires
Bobcat Poly-Fill Tires
Bobcat Severe-Duty Tires
Bobcat Super Float Tires
Cab Enclosure w/Heater Catalytic Purifier
Gold Package Option Counterweight Kit Deluxe Instrument Panel

Flasher/Strobe Lights

Positioning² Keyless Start System Power Bob-Tach™ Rear Auxiliary Hydraulics Ride Control Service Safety Training Kit Side Windows Skid-Steer Loader Operator Training Kit Sound Package Special Applications Kit³ Suspension Seat (Vinyl o Water Kit

Front & Rear Lights

Lift Arm Support

Warning Lights

Spark Arrestor Muffler

10-16 5 Standard

Duty Tires

Hydraulic Bucket

Meters/Gauges/

Parking Brake

Seat Bar

Seat Belt

The Attractively-Priced **Bobcat S130 Skid-Steer Loader**

The S130 is a smart way to move into the popular Bobcat line of skid-steer loaders. The machine offers top value for your money. It has a turning radius of 6 feet and a rated operating capacity of 1300 pounds, along with features such as heavy-duty drive chains that never need adjustment, removable axle hubs for quick, easy servicing and a dual-path cooling system that cools with debris-free air. The S130 also works with a wide variety of Bobcat attachments, and sells for a very attractive price.

The Multi-Purpose Bobcat \$130 Skid-Steer Loader

A hard-working machine, the S130 is loaded with time-saving, money-saving features. Here are just a few:

- · Great balance of power and maneuverability.
- . Choice of seven bucket styles and more than 30 other attachments.
- Bobcat Interlock Control System (BICS)™ is standard.
- · Operator-friendly cab.

Greater Comfort

The cab is designed with the operator in mind, for optimum comfort and functionality. And with a wider opening, it's easy to enter and exit.

The seat bar pivots from the rear, providing secondary restraint protection as well as a comfortable armrest for operators of all sizes. Plus, the worklight design doubles the amount of illumination to the work area for better operation in low light.

The S130 also features an easy-to-read, highly functional instrument panel, along with a number of improved comfort options.

1300 LB. 109.1 IN.

Rated Operating Capacity; 1400 lb. with optional counterweight kit

46 HP Lift Height

Liquid-Cooled Kubota Diesel Engine

Optional Deluxe Instrument Package includes:

- Multi-language capability
- · System diagnostic capability
- · All gauges read in metric or English units
- · Keyless start security
- Job clock
- · Real-time clock
- Help screens

NOTE — Where applicable, dimensions are in accordance with Society of Automotive Engineers (SAE) and ISO standards. Specifications and design are subject to change without notice. Pictures of Bobcat loaders may show other than standard equipment. All dimensions are given for loader equipped with standard tires. All dimensions are shown in inches. Respective metric dimensions are enclosed by parentheses. Bobcat Company complex with the consideration of 180-080. complies with the requirements of ISO 9001 as registered with BSI.

- Operating capacity rated with standard digging bucket according to SAE standard J818 - OPERATING CAPACITY TO EQUAL NO MORE THAN ONE-HALF THE TIPPING LOAD.
- Bucket positioning helps operator keep the same tilt of the load during lifting.
- Includes I exan front door, top and
- Special application kit (see #3) must be used.
- A 10-16.5 Tires 60.3 in. (1524 mm) or 54 in. (1372 mm) with inset rims 31.5 x 13-16.5 60 in. (1524 mm)
- B 10-16.5 Tires 50.3 in. (1278 mm) or 44 in. (1118 mm) with inset rims. 31.5 x 13-16.5 46.3 in. (1176 mm)
- C 54 in. Bucket Width 55.0 in. (1398 mm) 62 in. Bucket Width 62.0 in. (1575 mm)

761 mm) 139 2 in 109.1 in. (2771 mm) 77.0 in. 84.6 in (2148 mm 26° 35.5 in. 35.5 in. (900 mm) 96.3 in. (2445 mm 120.5 in.



Bobcat Company P.O. Box 6000 • West Fargo, ND 58078 www.bobcat.com

Printed in U.S.A.

An (IR) Ingersoll Rand business

Kn-30M-1203-#640493-F

Bobcat Attachments for this model:

Angle Broom*

Augei

Backhoe

Brushcat¹ **Rotary Cutter**

Brush Saw

Buckets

Chipper' Combination

Concrete Mixer³

Cutter Crusher

Diager

Dozer Blade*

Dumping Hopper

Farm Grapple (for use with utility forks or bucket)

Front Scarifier

Grader*

Hydraulic Breaker4

Pallet Fork

Industrial Grapple

Landplane

Landscape Rake

Mower

Pallet Fork

Planer*

Rear Stabilizer

Scraper

Snow Blade

Snowblower*

Sod Laver

Soil Conditioner*

Spreader Sweeper

Three Point Hitch

Tiller

Tilt-Tatch Tracks

Trench Compactor

Trencher

Utility Fork Vibratory Roller

Whisker Push Broom

Kit required