

MACHINE SPECIFICATIONS

TRUXTA BENDI - MACHINE SPECIFICATIONS			
Model	Petrol B300G (Petrol B450G)	Diesel B300D (Diesel B450D)	Electric B300E (Electric B450E)
Engine/Motor/Power (kW)/hp	Honda GX 160 3.6 / 4.8 Honda GX200 4.1 / 5.5	Yanmar L48 3.5/ 4.7 Yanmar L48 3.5 / 4.7	DC Brushless Motor 1000W /24v Motor 1300W / 24v
Fuel Type	Unleaded Petrol (4 stroke)	Diesel	2 x 12v Batteries
Fuel Capacity	3.1 litres / 0.682 gal	2.5 litres / 0.55gal	
Max Payload (kg)	300kg/660lbs/ 7ft ³ / 0.2m ³ (450kg/990lbs /10.6ft ³ / 0.3m ³)	300kg/660lbs /7ft ³ / 0.2m ³ (450kg/990lbs/10.6ft ³ / 0.3m ³)	300kg /660lbs/ 7ft ³ / 0.2m ³ (450kg/990lbs/ 10.6ft ³ / 0.3m ³)
Unladen Weight kg unladen weight lbs	170 (180) 374 (396)	201 (219) 442 (482)	224 (255) 493 (561)
Working Gradient	25°	25°	25°
	Working Gradients – See general safety notes on next page		
Drive & Controls	Hydrostatic System		24v Motor Gearbox
Brake System	Hydrostatic brake system with fail-safe dead-man handle		
Standard Fitment Tyres	Flotation with option for turf tyres		
Travel Speed Fwd/Reverse	0.4 mph forward / 6.44kph 0-1.5 mph / 2.42kph		0-3.5 mph/ 5.63kph 0-1.5 mph / 2.42kph
Noise Level (db.)	<94 (< 96)	< 100	< 69
Hand Arm Vibration	3.6 m/s ² 4.6 m/s ²	3.8 m/s ² 3.8 m/s ²	2.5 m/s ² 2.5 m/s ²
All dimensions unless otherwise stated are in mm and inches			
We reserve the right to change specification without prior notice.			
A 12 month warranty is applicable on all TRUXTA machines.			